



196.3200 | Two Output Shower W/ Shower Head & Tub Spout



COMPONENTS

- HS1020 - 7" Shower Arm
- HSB.6S - 6" Shower Head
- 196.2100T - Shower Trim
- PBV.1005A - Shower Valve
- 196.2300 - Tub Spout

SHOWER VALVE:

- Pressure balance shower valve
- Valve includes service stops
- Lift bottom handle to control volume
- Turn left for hot, right for cold.
- Top handle controls water diversion
- 1/2" NPT

SHOWER HEAD:

- Single function
- Solid brass construction
- 1.8 GPM flow rate

TUB SPOUT:

- Solid Brass construction
- 1/2" male NPT connection

STANDARDS:

- ASME A112.18.1 / CSA B125.1


See individual component specification sheets on following pages for further details.

HS1020 | Square Shower Arm




SPECIFICATIONS:

- Solid Brass Shower Arm
- With Sliding Flange



Technical Diagram




HSB.6S | 6" Brass Shower Head




SPECIFICATIONS:

- Solid Brass Shower Head
- Scrub rubber nozzles to easily clean water sediment
- 1.8 GPM Flow Rate
- 81 Nozzles
- Use with HS1020 Shower Arm




Technical Diagram




196.2100T | Tub / Shower Trim

SPECIFICATIONS:

- Solid brass construction
- Valve not included- trim only
- Lift Handle to control volume. Turn left for hot, right for cold.
- Small knob controls 2-way water diversion
- Extension Available - PBV.2100E**



Technical Diagram



PBV1005A | Pressure Balance Valve With Integrated 2-Way Diverter Page 1 of 2




SPECIFICATIONS:







- Lift Handle to control volume. Turn left for hot, right for cold.
- Knob controls 2-way water diversion - shared output.
- Pressure Balance Valve Flow Rate - 5.5 GPM @ 60 PSI
- Extension Available - PBV.2100E**

STANDARDS:

- ASME A112.18.1 / CSA B125.1




Technical Diagram




PBV1005A | Pressure Balance Valve With Integrated 2-Way Diverter Page 2 of 2




Water Diversion Diagram



Diverter Position = Left



Diverter Position = Middle
Shared Flow is Low Transition Flow



Diverter Position = Right

196.2300 | Tub Spout / Filler




SPECIFICATIONS:



- Solid Brass Construction
- 1/2" Female NPT Connection

STANDARDS:

- ASME A112.18.1 / CSA B125.1



Technical Diagram



Male / Female extension
available in 1" Increments.

