

## SDH.1070 | 14" Shower Door Handle



### SPECIFICATIONS:

- Solid Brass construction
- Fits 3/8" to 1/2" Thick Glass
- Mounting Centre to Centre: 14"
- Handle Thickness: 25mm





### **GLASS CUTOUT DETAILS**

14" Shower Door Handle Item No: SDH.1070



 $\label{eq:torserv} \begin{array}{c} \mbox{Tolerance:} \pm 0.1 \\ \mbox{Glass Thickness: } 3/8in \ [\sim 10mm] \ to \ 1/2in \ [\sim 12mm] \end{array}$ 

# **FLUSSO** LUXURY PLUMBING FIXTURES

# **Universal Fixtures**<sup>™</sup>

#### CARE & CLEANING GUIDELINES:

For optimal maintenance of your shower door hardware, adhere to the following guidelines:

- Regularly dry your shower door with a soft towel or cloth to preserve its original finish.
- Avoid using harsh cleaners or chemicals on the hardware, as the components may be coated with a clear lacquer that can incur irreparable damage.
- Prior to cleaning the entire hardware surface, conduct a patch test with your chosen cleaning solution in an inconspicuous area.
- Clean surfaces with a soft, dampened cloth or sponge, and thoroughly rinse with warm water after applying a small amount of gentle cleaning solution.
- Under no circumstances should abrasive products, sponges, or wire scrub brushes be used during the cleaning process.

#### MAINTENANCE :

- Hinges are supplied pre-greased at the factory to ensure a quiet and trouble-free operation.
- Should any squeaking become noticeable post-installation, it is advisable to apply a few drops of multi-purpose oil to the hinge, specifically at the nylon washer/pivot location. This lubricant will effectively permeate the hinge crevices, reducing friction and removing any accumulated grime or debris.
- Please refrain from using spray lubricants. In the event that the hinge needs to be disassembled for maintenance purposes, a small amount of white lithium grease should be applied to lubricate the interior hinge components.

### FRONT VIEW

SIDE VIEW





### FIT REPRESENTATION

